15 HP | 57 cfm Enclosed Rotary Screw

Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation

CDR Compressor

Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads

■ Free freight in the 48 states & southern Canada




Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
R153ENC	3	208-230-460	N/A	Basic	32	28	42	42	21
R153ENC-CDR	3	208-230-460	80 Gallon Horizontal	CDR	68	28	42	42	21

No Start Up Kit Required Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.





69 dBA

54 cfm @ 150 psi

57 cfm @ 125 psi