

NEW!
EASY TO USE!



MW-200

200 LBS. CAPACITY TIRE and WHEEL LIFT

Why MW-200?

Features :

- 200 lbs. capacity at 100 psi
- Reduces risk of shoulder and back injuries while limiting potential worker's comp claims
- Air operated with no batteries
- Air tool connection to reduce hoses in shop
- Easy to maneuver, extra strong steel construction that's made in the USA

Tires roll with little effort on the two rollers, providing easy alignment of the wheel and hub

Offset column for full access to lug nuts provide easy and quick transfer to wheel balancer

High quality 5" locking rear wheel casters rotate for maximum maneuverability with minimal rolling resistance

Single lever control and valve – provides responsive and easy positioning

Needle valves adjust the raise and lowering speeds

Includes air hose and auxiliary air tool connection

Solid plastic roller to protect tires

Tray for parts and holding lugnuts



SPECIFICATIONS

Part # MW-200
 Lifting Capacity: 200 lbs
 Color: Blue
 Weight: 135 lbs
 Height: 61 - 1/2"
 Width: 30 - 1/2"
 Length: 30"
 Tire size: 20" - 30" (Approx.)
 Stroke: 40"
 Rise Time: 6 seconds
 Operating Pressure: 100PSI
 Some assembly required



NEW!
EASY TO USE!



MW-500

500 LBS. CAPACITY TIRE and WHEEL LIFT

Why MW-500?

Features :

- 500 lbs. capacity at 100 psi
- Reduces risk of shoulder and back injuries while limiting potential worker's comp claims
- Air operated with no batteries
- Redundant lifting cables contained inside column for added safety
- Air tool connection to reduce hoses in shop
- Includes pressure regulator to prevent overloading
- Easy to maneuver, extra strong steel construction that's made in the USA



Hole for tie-down strap to hold tire in place. Tie strap included.

High quality 5" rear wheel casters rotate for maximum maneuverability with minimal rolling resistance

Single lever control and valve – provides responsive positioning

Needle valves adjust the raise and lowering speeds

Includes air hose and auxiliary air tool connection

Two solid plastic top support rollers for added stability and tire protection

The back stop allows 5" of adjustable height to accommodate a wide variety of tire sizes

Split rollers on bottom arms for dually tires



Tray for parts and holding lugnuts



Rotary World Headquarters

2700 Lanier Drive
Madison, IN 47250, USA
www.rotarylif.com

FIND US ON



Contact Information

Sales: p 800.640.5438
f 800.578.5438
e userlink@rotarylif.com
Tech. Support: p 800.445.5438
f 800.822.6502
e userlink@rotarylif.com



Contract Holder

FSS Contract GS07F8963D



Lit# MW200_MW500_Cutsheet_2013.10
©2013 VEHICLE SERVICE GROUP™. Printed in U.S.A.,
All Rights Reserved. Unless otherwise indicated,
ROTARY LIFT, VEHICLE SERVICE GROUP™, DOVER
and all other trademarks are property of Dover
Corporation and its affiliates.

SPECIFICATIONS

Part # MW-500
Lifting Capacity: 500 lbs
Color: Blue
Weight: 336 lbs
Height: 72"
Width: 42"
Length: 47 - 1/2"
Stroke: 40"
Tire Size: 30 - 45" (Approx.)
Rise Time: 6 seconds
Operating Pressure: 100PSI
Some assembly required